

Specification	Imperial	Metric
Safe Working Load	500 lbs	227 kgs
Maximum Overall Length	57.5 inches	1460 mm
Minimum Overall Length	55.1 inches	1400 mm
Maximum Overall Height	81.3 inches	2065 mm
Minimum Overall Height	57.5 inches	1460 mm
Spreader Bar - Maximum Height	75.2 inches	1910 mm
Spreader Bar - Minimum Height	16.9 inches	430 mm
Height at Maximum Reach	51.5 inches	1310 mm
Reach at Maximum Height	25.6 inches	650 mm
Reach at Minimum Height	15.7 inches	400 mm
Maximum Reach (centre of spreader bar to front of the mast)	36.6 inches	930 mm
Turning Radius	64.2 inches	1630 mm
Legs Open - External Width	45.2 inches	1150 mm
Legs Open - Internal Width	40.1 inches	1020 mm
Legs Closed - External Width	26.4 inches	670 mm
Legs Closed - Internal Width	21.6 inches	550 mm
Overall Height of Legs	4.7 inches	120 mm
Ground Clearance	1.4 inches	35 mm
Front Twin Castors	4.0 inches	100 mm
Rear Braked Castors	4.0 inches	100 mm
4 Point Positioning Cradle - Maximum Height	61.0 inches	1550 mm
4 Point Positioning Cradle - Minimum Height (usable)	15.4 inches	390 mm

Weights	Imperial	Metric
Mast, Base & Boom Assembly (includes 6 point spreader bar)	81.4 lbs	37.0 kgs
Power Pack	6.6 lbs	3.0 kgs
Total (including 6-point spreader bar)	88.0 lbs	40.0 kgs
Base Assembly (excluding battery)	44.0 lbs	20.0 kgs
Mast & Boom Assembly (excluding battery)	37.4 lbs	17.0 kg
4 Point Positioning Cradle (manual operation)	13.2 lbs	6.0 kgs
4 Point Positioning Cradle (powered operation)	19.8 lbs	9.0 kgs

Specifications may vary due to manufacturing tolerances

Electrical Specifications (Lift)

Battery 1 x 12 volt rechargeable sealed lead acid type
 Battery capacity 3.2 Ah
 Charger rated input 230V AC 50/60Hz
 Charger rated output 27.4/29.0 V DC@0.8A

Electrical Specifications (Powered cradle only)

Battery 24V DC rechargeable NiMH sealed
 Battery capacity 1400 mAh
 Charger rated input 100 - 240V AC / 24 V DC 50/60Hz Max. 75mA
 Charger rated output Max 28.4V DC

Warranty

The Presence comes with a 2 year warranty as standard.
 Please refer to your user manual for further information.


Electrical Shock Protection

Charger - class II
 Lift - internal power source

Degree of shock protection
 Charger - Type B
 Lift - Type B
 Intended operating environment : >+5° <+40°
 Outside this environment functionality and safety may be compromised



Oxford®



Joerns Healthcare Limited
 High Street, Wollaston, Stourbridge, West Midlands DY8 4PS England
 (T) +44 (0)1384 446622 (F) +44 (0)1384 446601
 www.joerns.co.uk • email: info@joerns.co.uk