

Voyager Overhead Hoist	420	550	800
Safe Working Load	190kg / 420lbs / 30st	250kg / 550lbs / 39st	360kg / 800lbs / 57st
Soft Start and Stop	✓	✓	✓
Emergency Lower	Manual / Electric	Manual / Electric	Manual / Electric
Emergency Stop	✓	✓	✓
Low Battery Indicator	Visual / Audible	Visual / Audible	Visual / Audible
Battery Capacity (load of 75kg)	Upto 150 transfers	Upto 150 transfers	Upto 150 transfers
Battery Charger	Integrated	Integrated	Integrated
Weight (including battery)	12.7kg / 28lbs	22.7kg / 50lbs	22.7kg / 50lbs
Compatible with Full Oxford Sling Range	✓	✓	✓
Vertical Speed	4cm/sec	6cm/sec	3cm/sec
Horizontal Speed	15cm/sec	15 and 25cm/sec	15 and 25cm/sec

Accessories	Code
Infrared Kit	VOY-A5400
Powered Turntable - 45 Degree	VOY-A4000-45-UK
Powered Turntable - 90 Degree	VOY-A4000-90-UK
Automatic Return to Charger	VOY-A5200
X-Y Tracking System	VOY-A5800 & VOY-A5810
Gantry Track	VOY-A9200

Track	Code
2m Straight Track	VOY-M0580
3m Straight Track	VOY-M0585
45 Degree Curve	VOY-A0175
90 Degree Curve	VOY-A0170
Track Bracket	VOY-A0110
Wall Bracket (set of 2)	VOY-A4900
Swivel Wall Bracket (set of 2)	VOY-A4950
Lateral Bracket for Suspended Ceiling	VOY-A0553
Additional Rail Stopper	VOY-A5320

Specifications may vary due to manufacturing tolerances

More track options available. Please contact Customer Services for more information.

Suitability

The Voyager range of lifts are suitable for the following categories of lift within the working parameters of the lifts specified in the technical specifications:

- Category A - Wheelchair
- Category B - Bed
- Category C - Bath
- Category D - Toilet/Shower Chair
- Category E - Floor
- Category F - 90 degree rotation

Approvals & Certification

- CSA 601.1
- UL 2601.1
- EN 60601.1
- EN ISO 10535 (Lifting devices) SGS
- UK Test Report: DUR22107/AC/OO

Electrical Specifications

- Battery 1 X 12 volt rechargeable sealed lead acid type
- Battery capacity 3.2 Ampere hours
- Charger rated input 230Vac 50/60Hz
- Charger rated output 27.4/29.0 VDC@0.8A

Warranty

The Voyager system comes with a 12 month warranty as standard. Please refer to the user manual for further information.

Electrical Shock Protection

- Charger - class II
- Lift - internal power source

- Degree of shock protection
- Charger - Type B
- Lift - Type B
- Intended operating environment : >+5° <+40°
- Outside this environment, functionality and safety may be compromised





Joerns Healthcare Limited
 High Street, Wollaston, Stourbridge, West Midlands DY8 4PS England
 (T) +44 (0)1384 446622 (F) +44 (0)1384 446601
 www.joerns.co.uk • email: info@joerns.co.uk